

ISOGROUT 3030

Product Data Sheet

Description:

ISO GROUT 3030 is a polymer-rich cementitious tile joint filler. It is a blend of selected cement, graded filler, and selected polymers which when mixed with water forms a durable and tough joint filler that can be used for

Uses:

Iso grout can be used to fill the joints of tiles, marbles or granites where the joint width does not exceed 4mm .

Advantages:

- ISO GROUT is water resistant, crack free up to 4mm wide joints.
- Available in white & grey .Other colours are available on request .
- Ideal for both interior and exterior use.
- Non fading ! colour is specially formulated with selected pigments so that fading does not take place over a period of time.
- Rigid filler ! it has strong bonding properties so that the grout remains in place permanently without wear.

Technical Properties:

| | |
|------------------------|--|
| Base : | High grade cement modified with special polymers |
| Colour : | Grey, White and other colour on request. |
| Density : | 1.8gm/cc |
| Compressive Strength : | 15-20 N/mm ² at 28 Days (15-20 Mpa) |
| Tensile Strength : | 2.75 N mm ² at 28 days (2.75 Mpa) |



Application procedure:

Surface preparation

ISO GROUT can be applied after a minimum of 24 hours from tiling. All tiles should be securely fixed and cleaned before applying ISO GROUT

Mixing

Mixing can be done using a slow speed drill fitted with a paddle .Approximately 3 to 3.5 liters of water is required for 10 kg of ISO GROUT. Take measured quantity of water in a container, add ISO GROUT gradually and mix until a uniform lump free paste like consistency is obtained. For critical areas like swimming pools and other water retaining areas ISO GROUT modified with ISO BOND S.B.R 1030.

(1 liter ISO BOND S.B.R per 10 kg ISO GROUT + balance amount of water) is recommended.

Application

Apply Iso grout to the tile joints using a putty blade or scraper. Work the material into the joints and fill the joints completely .Remove the surplus material with a cloth and run a rounded tool along the grout to level it. The product can be used up to 2 hours after mixing.

Standards :

ANSI 118.6 1192, BS 5980



ISOBIT

Coverage:

1 kg of isogROUT is sufficient for grouting joints 28 running meter long, 4mm wide and 3mm deep.

Cleaning:

Clean all tools and application equipment with clean water immediately after use. Hardened / cured material can only be removed mechanically.

Packing:

Available in 20 kg bags .

Storage:

Store under cover, out of direct sunlight and protect from extreme temperatures. In tropical climates the product must be stored in air-conditioned environment.

Shelf life:

Shelf life is up to 12 months when stored as per recommendations.

Health and Safety:

As with all construction chemical product, caution should be always exercised. Protective clothing such as gloves and goggles should be worn. Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally allowed, do not induce vomiting, but call for medical assistance immediately.



ISOBIT

قبل كل استخدام لأي منتج من منتجات ISOBIT أو فروعها أو الشركات التابعة لها بالعلامة ("ISOBIT") يجب على المستخدم دائماً قراءة ومتابعة التعليمات والتحذيرات والتعليقات على أحدث تسمية للمنتج عن طريق ورقة بيانات المنتج الموجودة على الموقع www.isobitiraq.com أو عن طريق الاتصال بقسم الخدمات الفنية للشركة (إيزوبيت) +9647501136936 . لا يوجد في أي منشورات أو مواد إيزوبيت ما يخفف من التزام المستخدم بقراءة ومتابعة التعليمات والتعليقات الخاصة بكل منتج من منتجات إيزوبيت على النحو المنصوص عليه للمنتج الحالي. تضمن إيزوبيت هذا المنتج لمدة عام واحد من تاريخ التثبيت ليكون خالياً من عيوب التصنيع وتلبية الخصائص التقنية الموجودة في ورقة بيانات المنتج -النشرة الفنية- الحالية إذا تم استخدامها وفقاً للتوجيهات خلال فترة صلاحية المنتج. يحدد المستخدم ملائمة المنتج للإستخدام المقصود وتحمل جميع المخاطر. يقتصر التعويض الوحيد للمستخدم و / او المشتري على سعر الشراء أو استبدال هذا المنتج بإستثناء أي تكاليف للعمليات . لا توجد ضمانات أخرى صريحة أو ضمنية.

T1: +964 750 1136 936.
T2: +964 751 740 1493.
E: info@isobitiraq.com.

ISOBIT for Building Chemicals

www.isobitiraq.com



C.R 13869 I.R 12308